

TITAN™ Antifreeze & Coolant Prediluted 50/50



With Advanced Temperature & Corrosion Protection

TITAN™ Antifreeze & Coolant Prediluted 50/50 is an antifreeze/coolant formulated with a borate-based inhibitor additive package, including nitrite, for superior protection against liner pitting, corrosion, and scale formation. It provides maximum temperature control, preventing freeze-up and boil-over. It is suitable for use in heavy duty and light duty engines, including Caterpillar, Detroit Diesel, and Cummins.

TITAN™ Antifreeze & Coolant is free of phosphates and contains low levels of silicate.



FEATURES

- Compatible for use in heavy duty and light duty applications
- Protects against liner pitting, corrosion, and scale formation
- Ready-to-use formula eliminates mixing errors and water quality issues that harm engines
- Can be used when topping off without adding additional SCAs (supplemental coolant additives)

Formulated to meet or exceed specifications:

ASTM D-3306	Detroit Diesel 7SE298	Navistar
ASTM D-4985	EMD M.I. 1748E	New Holland 9-86
ASTM D-6210	Freightliner 48-22880	Paccar
Case MS1710	GM 1825	SAE 1941
Caterpillar	GM 1899	TMC RP329
CID A-A 52624A	John Deere 8650-5	Volvo GM
Cummins CES 14603	Mack	Waukesha 4-1974D

Properties	Typical Values	Test Method
Specific Gravity, 68°F	1.052–1.084	ASTM D-1122
pH	10.2–10.8	ASTM D-1287
Foam (mil/sec)	100/3 max	ASTM D-1881
Total Water*, Wt. %	48% max	ASTM D-1123
Total Glycol, Wt. %	50% min	ASTM D-202
Total Inhibitors, Wt. %	1% min	

* Deionized

Protection Chart

Concentration	50%
Boiling Point†	265°F
Freezing Point	-34°F

†Using conventional 15 psi radiator cap.

Formulated with bitterant agents to discourage ingestion by humans or animals.

READY-TO-USE.
Do not mix with water.



WATERFORD
OIL CO., Inc.

Tel: 507-645-5659
www.waterfordoil.com